




MILE POSTS

D-754-20



NOTES:

Installation: Posts are to be installed along right shoulder in line with delineators.

Spacing: Mile posts shall be placed at the locations shown in the plans.

Mile Sign Backing: Backing shall be fabricated of 0.080 aluminum. Sheets shall conform to section 894.01 of the Standard Specifications.

Posts: Posts shall conform to section 894.05 of the Standard Specifications.

Fasteners: The mile signs shall be attached to the post by tension pin type fastener or other suitable vandal resistant non-rust fastener.

Reflective Sheeting: Sheeting shall conform to section 894.02 (Type III) of the Standard Specifications.

Mile Numbers: Mile numbers shall be of the series shown and may be screened or applied copy. Screening and reflective sheeting or applied copy shall conform to section 754 & 894 of the Standard Specifications.

Background and message shall be reflectorized.

Method of measurement: The number Mile Posts completed in place and accepted by the Engineer.

Basis of Payment: The number of Mile Posts. The unit price bid for Mile Post shall be full compensation for furnishing, delivering and installing Mile Post and shall include message panel, post, hardware and equipment necessary to complete the work in a satisfactory manner.



NORTH DAKOTA DEPARTMENT OF TRANSPORTATION	
10-1-86	
REVISIONS	
DATE	CHANGE
08-03-87	Notes
05-01-92	General revision
08-26-97	Spacing note
01-09-98	Post size
02-28-01	Post offset anchor size
10-23-02	Sign panel revision
02-28-03	Sign punch location
12-01-04	PE Stamp added
04-05-06	Revised anchor plate

This document was
originally issued
and sealed by
MARK S. GAYDOS,
Registration Number
PE-4518,
on 04/05/06 and the
original document
is stored at the North
Dakota Department
of Transportation